



Systemair CB 400-6,0 400V/2 Duct heater

[Більш детальна інформація в нашому онлайн-каталозі](#)

Артикул: 5391
Виробник: Friso
Код товару: CB

від 25121 грн.

Опис

Electrical duct heater

Duct heater with spigot connection for standard spiral circular ducts. Manufactured from Aluzinc-coated sheet steel with a heating element in stainless steel. The CB heater has rubber seals on the connecting spigots.

The heater has double integral overheating protection: one with automatic and one with manual reset. Suitable for control by room thermostat or Pulsar regulator (additional accessories).

The minimum air volume is based on a minimum air velocity of 1.5 m/s. These duct heaters are designed for a maximum output air temperature of 50°C.

The CB can be installed in a horizontal or vertical position. In a horizontal position, the connection box should be installed facing upwards, or rotated 90° to one side. Installation with the connection box facing downwards is not allowed.

Документація

- [CB-CBM-CBMF ИНСТРУКЦИЯ ПО МОНТАЖУ.pdf \(656.52 KB\)](#)
- [CB-CBM-CBMF ИНСТРУКЦИЯ ПО МОНТАЖУ.pdf \(656.52 KB\)](#)
- [CB-CBM-CBMF ИНСТРУКЦИЯ ПО МОНТАЖУ.pdf \(656.52 KB\)](#)
- [CB-CBM-CBMF ИНСТРУКЦИЯ ПО МОНТАЖУ.pdf \(656.52 KB\)](#)
- [DECL OF CONFORMITY CB_CBM_CBMF_CBMB_2020-09.PDF \(637.39 KB\)](#)
- [DECL OF CONFORMITY CB_CBM_CBMF_CBMB_2020-09.PDF \(637.39 KB\)](#)
- [DECL OF CONFORMITY CB_CBM_CBMF_CBMB_2020-09.PDF \(637.39 KB\)](#)
- [DECL OF CONFORMITY CB_CBM_CBMF_CBMB_2020-09.PDF \(637.39 KB\)](#)

Характеристики

Основні характеристики	
Холодопродуктивність (Min-Max), кВт	Електрический нагреватель
Електричне нагрівання	
Підвищення температури, повна потужність, максимальна витрата повітря, °C	2~
Номінальні дані	
Клас герметичності	6 000
Номінальна потужність на валу (P2), кВт	Круглий
Тип підключення повітроводу	макс. 30
Номінальні параметри	
Макс. розсіювана потужність, Вт	15
Розмір повітроводу: Круглий, вихід, мм	AC
Споживаний струм, А	50
Частота, Hz	400
Расход воздуха	
Звуковий тиск (LpA), дБ(A)	мін. 678
Розміри та вага	
Витрата повітря, м³/год	7,2
Канальний охолоджувач/нагрівач	400
Торгове найменування	400