

## Systemair VLC 704

[Більш детальна інформація в нашому онлайн-каталозі](#)

Артикул: CVLC0704  
Виробник: Frisco  
Код товару: VLC

від 0 грн.



### Опис

#### Technical features

- 6 sizes
- Cooling capacity from 174 to 347 [kW]
- Fans versions: STD (Standard), HSE (High seasonal Efficiency), HT (High Temperature), HPF (High Pressure Fans)
- Acoustic versions: BLN (Basic Low Noise), LN (Low Noise), ELN (Extra Low Noise)
- Two refrigerant circuits
- 4 Scroll compressors
- Finned tubes coils

#### Standard features

- Phase sequence control
- Control circuit transformer
- Control data logger
- Modbus protocol kit for BMS
- Fan speed control for low ambient operation

#### Factory installed options

- Lonwork protocol kit for BMS
- Bacnet protocol kit for BMS
- Compressor soft-starter
- Power factor correction capacitors
- Compressor overload protection
- Automatic circuit breaker
- HP & LP gauges
- Condenser coils with copper fins
- Chiller grilles
- Compressor jackets

#### Field installed accessories

- Remote ON/OFF control
- Remote keyboard panel
- Anti-vibration spring

### Документація

- [CD\\_VLC\\_704-1204.dwg \(967,61 KB\)](#)
- [CD\\_VLC\\_704-1204.dwg \(967,61 KB\)](#)
- [CD\\_VLC\\_704-1204.dwg \(967,61 KB\)](#)
- [CD\\_VLC\\_704-1204.dwg \(967,61 KB\)](#)
- [EDM\\_VLC-S.2GB08.16.pdf \(1.13 MB\)](#)
- [EDM\\_VLC-S.2GB08.16.pdf \(1.13 MB\)](#)
- [EDM\\_VLC-S.2GB08.16.pdf \(1.13 MB\)](#)
- [EDM\\_VLC-S.2GB08.16.pdf \(1.13 MB\)](#)
- [IOM\\_VLH-VLC\\_704\\_1204.pdf \(3.2 MB\)](#)
- [IOM\\_VLH-VLC\\_704\\_1204.pdf \(3.2 MB\)](#)
- [IOM\\_VLH-VLC\\_704\\_1204.pdf \(3.2 MB\)](#)
- [IOM\\_VLH-VLC\\_704\\_1204.pdf \(3.2 MB\)](#)
- [TS\\_VLS\\_H\\_C\\_604-1204\\_GB\\_0617.PDF \(187,46 KB\)](#)
- [TS\\_VLS\\_H\\_C\\_604-1204\\_GB\\_0617.PDF \(187,46 KB\)](#)
- [TS\\_VLS\\_H\\_C\\_604-1204\\_GB\\_0617.PDF \(187,46 KB\)](#)
- [TS\\_VLS\\_H\\_C\\_604-1204\\_GB\\_0617.PDF \(187,46 KB\)](#)

### Характеристики

Електричне нагрівання	
Підвищення температури, повна потужність, максимальна витрата повітря, °C	3~
Номінальні параметри	
Споживаний струм, А	50
Частота, Hz	400
Параметри звуку	
Витрата повітря при макс. продуктивності, м³/год	72
Продуктивність	
Коефіцієнт EER, W/W	199
Рівень звукового тиску з відривом 1 м, зовнішній блок, дБ(А)	3,16
Розміри та вага	
Витрата повітря, м³/год	1 367